



**HEIGHT  
SAFETY**

# CONFINED SPACE RESCUE KIT

The LINQ Confined Space Rescue Kit has been designed specifically for rescue from confined spaces.

It can easily be set up by one person and easy to transport.

The 25m wire rope winch is ideally suited to rescue applications and confined space work.

Must be manually wound to raise or lower - can raise or lower 25m down.

Supplied with bracket for tripod.

Complies to Australian standards AS/NZS 1891 and AS 2865 -2009.



## CONFINED SPACE SPREADER BAR (HSCSSB)

The LINQ Confined Space Spreader Bar is designed for use with harnesses incorporating confined space loops or D-rings and is ideal for confined space entry/exit and rescue and retrieval applications. Comes with Snap Hook attachments to secure the worker.



## KIT BAG (HSKB710)

- Heavy duty waterproof duffel kit bag
- Secures and protects parts until next use
- Dimensions: 720mm x 320mm x 135mm

## TACTICIAN RIGGERS HARNESS (H201)

- Liqui-Pel Technology
- Pebble Weave webbing
- Slotted Buckles
- Integrated Suspension Trauma Strap
- Shoulder Confined Space/Rescue Loops
- Tangle-free back mesh
- Large Dorsal Dee Ring
- Front Belay Loops



## 2 x SCREW GATE KARABINER (KSGA18)

- Opening: 18mm
- Weight: 165gm
- Rating: 25kN
- Width: 58mm
- Length: 110mm



## TRIPOD RESCUE WINCH (HSTW25)

- For use with LINQ Tripod (HSTP29)
- Tested Load: 1350kg
- Rated Load: 135kg
- Maximum lifting: 25m
- Conforms to EN1496:2006



## CONFINED SPACE SIGN (DCSEB4530P)

- Size: 450 x 300mm
- Material: 1.4mm Polypropylene



## CONFINED SPACE TRIPOD (HSTP29)

- For confined space access, adjustable height 1.9m-2.9m, lifting load capacity 500kg, certified to EN795:2012
- Footprint: 1.8m diameter
- Weight: 15kg
- Anchorage rated to 12kN
- Steel support shoes with rubber sole for increased stability, comes with tripod bag

AUSTRALIA - 1300 LINQ HS (5467 47)

NEW ZEALAND - 0800 LINQ HS (5467 47)

