

## Force® Typhoon™ 8 Half Mask Respirator

BHT003-1L5-0AN / BHT003-0L5-0AN / BHT003-2L5-0AN / BHT008-4L5-0AN



Small | BHT003-1L5-0AN



Medium | BHT003-0L5-0AN



Large | BHT003-2L5-0AN



Short Wide | BHT008-4L5-0AN

### DESCRIPTION

The Force® Typhoon™ 8 twin cartridge half mask with Typhoon™ valve offers superior low breathing resistance and incorporates a 4-point suspension harness with quick release buckles.

The mask accepts the full range of Force® filters, including PressToCheck™ and PressToCheck™ Compact ranges, providing protection against particulates, select gases and vapours.

### SAFETY STANDARDS

- AS/NZS 1716

### FEATURES

- Durable thermoplastic rubber mask available in four sizes for superior fit to most face shapes. Fully adjustable 4-point cradle suspension ensuring an effective facial fit.
- The low-profile, swept-back design enables excellent visibility, allowing filters to be worn effectively behind all types of faceshield and welding visor.
- The Force® Typhoon™ 8 half mask has been meticulously engineered to incorporate a small number of key components. Disassembly, cleaning and maintenance are effortless with replacement parts available if necessary.
- Low resistance exhalation valve for easy breathing. Made from silicone it performs well at very low temperatures.
- Fully compatible with PressToCheck™ twin filter cartridges, providing daily face fit reassurance with the easiest way to check the seal each time the mask is donned. Fit it - Press it - Check it.
- Available in Small, Medium, Large and Short/Wide to provide an even better fit to a wider range of face sizes and shapes improving the seal and level of protection.

## SPECIFICATIONS

Usage  
**R**

Mask Design  
**Single Piece Over-Moulded Twin Filter Half Mask**



4 Point Harness adjustment system  
**Yes**

Mask Material  
**Thermoplastic Elastomer & Acrylonitrile Butadiene Styrene (ABS)**

Metal Free  
**Yes**



Exhalation Valve  
**Typhoon Valve**



Nose Bridge  
**Moulded**



BSI Kitemark  
**Yes**

Latex free  
**Yes**



Product Weight  
**M = 87g**

## APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Aerospace

Agricultural

Airports

Construction and Infrastructure

Facilities Management

Food and Drink Management

Hospitals, Healthcare & Pharmaceuticals

Law Enforcement

Manufacturing

Maritime

Mining Aggregates and Quarrying

Oil, Gas and Chemical Companies

Rail and Tunneling

Renewable, Wind and Solar Energy

Scaffolding and Roofing

Sole Trader

Utilities Contractors

Welding