

KARABINER SCREW GATE STEEL – 18MM



PART CODE: **KSGSA18**

The LINQ range of karabiners offer exceptional strength, manufactured under stringent quality control conditions. The KSGSA18 karabiner has an easy-to-use screw gate mechanism making connection to PPE and anchorage point effortless. High strength steel construction provides robust and safe connection.

PRODUCT FEATURES >

- High tensile drop forged steel.
- Self-closing with manual screw gate.
- Sleek design minimises snagging and damage to harness and lanyard webbing.
- >6kN gate strength. Top and side.
- Stringent ISO 10333-5 batch testing conducted to international standards.
- Black electrophoresis finish.

PRODUCT DETAILS >

- **Opening:** 18mm
- **Weight:** 165gm
- **MBS:** 25kN
- **Gate:** >6kN
- **Width:** 58mm
- **Length:** 110mm

APPLICATIONS >

Multiple applications: Agricultural, Chemical, Construction, Manufacturing, Mining Oil and Gas, Transportation, Utilities, Rope Access.

STANDARDS >

Conforms to and accepted under AS 1891.5:2020.
Min gate strength requirement of >6kN.



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice If in doubt please contact the LINQ helpline.*

PARAMOUNT SAFETY PRODUCTS AUSTRALIA
12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 546 747
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
7 SIR WOOLF FISHER DRIVE, Highbrook,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 546 747
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINQHS.COM
PARAMOUNTSAFETY.COM

HEIGHT SAFETY
FROM
PARAMOUNT SAFETY PRODUCTS