## PRATT FLAMMABLE LIQUID STORAGE CABINET: 30L - 1 DOOR - 1 SHELF

## PRATT INDOOR FLAMMABLE LIQUID STORAGE CABINETS COMPLY WITH THE AUSTRALIAN STANDARD **AS1940 "THE STORAGE AND HANDLING OF FLAMMABLE** AND COMBUSTIBLE LIQUIDS".

This range of cabinets is suitable for the storage of flammable or combustible liquids as classified by the United Nations criteria and the ADG Code for Dangerous Goods.

These include flammable liquids such as Paints, Solvents, Petrol, Thinners, Kerosene, Turpentine, White Spirits, Alcohol and Ethanol. Also, combustible liquids such as Diesel, Linseed Oil and Pine Oil.

## **FEATURES & BENEFITS:**

- Low profile under bench design.
- Constructed of double walled 1.2mm thick galvanised steel.
- Self closing door with speed adjustable hydraulic closure.
- 1 x 1.6mm thick, perforated, galvanised steel shelf.
- Continual stainless steel piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Flammable Liquid diamond and other decals applied.
- Optional additional shelves available.
- Includes set of 4 rubber feet.

- WEIGHT: 53ka - CAPACITY: 30L - DOORS:

1 (Inc. Base Level) - SHELVES:

- EXTRA SHELF: 5517-29S

EXTERNAL (MM)			INTERNAL (MM)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
770	515	465	525	420	370

NUTE:

1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING.

2. FORTOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT CLEARANCE LOCATIONS.







VOLUME CAPACITY	PER SHELF	TOTAL	
2L Winchester	6	6	
4L Winchester	4	4	
4L Paint Can	4	4	
20L Round Can	1	1	
Aerosol Can	30	30	

