# **PROTECTIVE EYEWEAR**

# PROTEUS 1 SAFETY GLASSES

PRODUCT DATA SHEET: 9500 | 9502 | 9509











PRODUCT CODE



## FEATURES AND BENEFITS

- AquaShield Hardened Anti-Fog Technology
- Cold formable arms for individual fit
- Dust Guard Di tech Lens provides dust and water protection
- Low profile arm to aid in use with other PPE
- Ultra soft TPR Anti-Slip Nose Pad
- SuperFlex arms ensure Low Clamp force reducing Temporal pressure
- UV400 100% UV Protection on Tinted Lens
- Certified Medium Impact Protection

### PRODUCT DETAILS

Lens Material: AS/NZS Medium Impact rated

Polycarbonate Base Curve 9

Lens Coating AquaShield Hardened Anti-Fog Hydrophilic Technology

Frame/Arms: Polycarbonate + TPR

Weight:

### **APPLICATIONS**

The Pro Choice Safety Gear range of eye protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments. The Proteus Range of protective eyeware also incorporates excellent protection from dust and excellent integration with other PPE.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, manufacturing, metal processing, mining and quarrying, transportation.

## **CLEANING INSTRUCTIONS**

Clean with warm soapy water or mild lens cleaning solutions. Do not use alcohol based cleaning wipes/solutions as this may damage the lens coatings.

### PARAMOUNT SAFETY PRODUCTS AUSTRALIA PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK. EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ











**AVAILABLE IN** 

| PRODUCT CODE | UOM  | MOQ | CTN QTY |
|--------------|------|-----|---------|
| 9500         | EACH | 12  | 144     |
| 9502         | EACH | 12  | 144     |
| 9509         | EACH | 12  | 144     |

### **CARE INSTRUCTIONS**

Avoid exposure to liquids/solvents that may cause the lens to distort/ craze as this may affect protection required.

Inspect prior to use for any pitted, crazed, damaged or heavily scratched lenses and replace if signs of deterioration appear.

For heavily soiled applications, wash under running water to remove excess grit and wipe clean with Pro Choice Safety Gear Lens Cleaning Wipes.

For product longevity store in a clean microfiber Pro Choice Safety Gear Spectacle Pouch.

### **STANDARDS**

### **CERTIFIED TO:**

AS/NZS 1337.1:2010 SAI Global LICENSE NUMBER-SMK 40226

AS/NZS 1337.1:2010 CLEAR LENS - CATEGORY 0 - 90% (Tv)

LUMINOUS TRANSMITTANCE- OUTDOOR UNTINTED SMOKE LENS - CATEGORY 3 - 15% (Tv)

LUMINOUS TRANSMITTANCE OUTDOOR TINTED LIGHT BROWN LENS - CATEGORY 1 - 54% (Tv) LUMINOUS TRANSMITTANCE- OUTDOOR UNTINTED

