


RESPIRATORY GEAR

FILTERSPEC™ PRO P2 REPLACEMENT MASK WITH CARBON FILTER

PRODUCT DATA SHEET: FSPG531



PRODUCT CODE:
FSPG531



FEATURES AND BENEFITS

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices
- Therapeutic Goods Administration (TGA) Listed
- P2 activated carbon disposable respirator for protection against nuisance level organic vapours, mechanically & thermally generated particles
- Lightweight cupped design for comfortable extended wear.
- Dual QuickLock head strap for ease of donning & doffing.
- ProValve exhalation valve for decreased breathing resistance & heat stress.
- Resealable bag for hygienic storage.
- Replacement respirator to be used in conjunction with FilterSpec Pro goggle/mask combo



WARNINGS AND USE LIMITATIONS

- Facial hair has the potential to compromise the required protective seal of the respirator
- Ensure adequate oxygen levels are present
- Ensure the contamination is known and the respirator is suitable for the application
- Replace when taste, smell or the breathing resistance is high
- Store in a clean, resealable storage device

AVAILABLE IN

PRODUCT CODE	QUANTITY	CARTON
FSPG531	10 pieces	20 boxes
FSPG	1 pair	20 boxes

STANDARDS

CERTIFIED TO:
AS/NZS 1716:2012 Respiratory Protective Devices
Certified by SAI Global

To be used in conjunction with: AS/NZS 1715:2009 -
Selection, use & maintenance of respiratory
protective equipment



AS/NZS 1716:2012
Lic 1508

PRODUCT DETAILS

Straps: Latex-Free Rubber Band
Filter Media: Polyester, P2 Carbon Spunbound
Weight: 15g ± 1

CARE INSTRUCTIONS

Shelf life of the unopened product is 3 years from date of manufacture when stored within temperature range of -20°C to +25°C & less than 80% relative humidity.

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

Ensure mask is correctly fitted prior to each use & conduct annual fit testing in accordance with AS/NZS 1715:2009.

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

RELATED PRODUCTS

PRODUCT CODE:
FSPG



FILTERSPEC PRO
GOGGLE / MASK COMBO
P2+VALVE+CARBON

PRODUCT CODE:
PC821



DUST MASKS
PROMESH P2

PRODUCT CODE:
PC823



DUST MASKS PROMESH
P2+VALVE+CARBON

PRODUCT CODE:
PCA1P2



A1P2 PRO CARTRIDGES
FOR HMTMP

PRODUCT CODE:
HMA1P2



ASSEMBLED HALF MASK
WITH A1P2 CARTRIDGES

AUSTRALIA:
1800 770 723

ADELAIDE:
(613) 9764 9900
SA@PARAMOUNTSAFETY.COM.AU

MELBOURNE:
(613) 9764 9900
VIC@PARAMOUNTSAFETY.COM.AU

SYDNEY:
(612) 9601 3877
NSW@PARAMOUNTSAFETY.COM.AU

NEW ZEALAND:
0800 770 723
NZ@PARAMOUNTSAFETY.CO.NZ

BRISBANE:
(617) 3806 2699
QLD@PARAMOUNTSAFETY.COM.AU

PERTH:
(618) 9301 7888
WA@PARAMOUNTSAFETY.COM.AU

PROCHOICESAFETYGEAR.COM

