

RESPIRATORY GEAR RESPIRATOR P1 WITH VALVE

PRODUCT DATA SHEET: PC315



PRODUCT CODE:
PC315



FEATURES AND BENEFITS

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- P1 disposable respirator for protection against mechanically generated dust particles.
- Lightweight cupped design for comfortable extended wear.
- Dual latex free elastic straps for ease of donning & doffing.
- ProValve exhalation valve for decreased breathing resistance & heat stress.
- Easily worn with glasses & goggles.
- Resealable bag for hygienic storage.

AVAILABLE IN

PRODUCT CODE	QUANTITY	CARTON
PC315	12 pieces	20 boxes

PRODUCT DETAILS

Straps: Latex-free rubber band
Filter Media: Polypropylene Melt-Blown
Weight: 13.8g + 1g each

CARE INSTRUCTIONS

Shelf life of the unopened product is 3 years from date of manufacture when stored within temperature range of -20°C to +25°C & less than 80% relative humidity.

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

Ensure mask is correctly fitted prior to each use & conduct annual fit testing in accordance with AS/NZS 1715:2009.



WARNINGS AND USE LIMITATIONS

1. Facial hair has the potential to compromise the required protective seal of the respirator.
2. Ensure adequate oxygen levels are present.
3. Ensure the contamination is known and the respirator is suitable for the application.
4. Replace when taste, smell or the breathing resistance is high.
5. Store in a clean resealable storage device.

STANDARDS

CERTIFIED TO:

AS/NZS 1716:2012 Respiratory Protective Devices
 Certified by Benchmark
 To be used in conjunction with: **AS/NZS 1715:2009** -
 Selection, use & maintenance of respiratory protective
 equipment



CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

APPLICATIONS

The Pro Choice Safety Gear range of respiratory gear is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, manufacturing, metal processing, mining and quarrying, transportation.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA
 12 FELLOWSHIP ROAD,
 GNANGARA, WA 6077
 TECH SUPPORT: 1300 275 820
 CUSTOMER SERVICE: 1300 770 723
 EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
 7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
 EAST TAMAKI, AUCKLAND 2013
 TECH SUPPORT: 0800 888 778
 CUSTOMER SERVICE: 0800 888 778
 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
 PARAMOUNTSAFETY.COM

